

EMERALD

# PORT TRAILER TYRES



## FEATURES

- Range of sizes for port terminal and industrial trailer applications
- Cut-Wear Resistant Cooler tread for round the clock operations
- Resilio layers for cushion ride
- Concave sidewall profile to reduce sidewall damages
- High Durometer, Interference-fit hardbase for excellent stability and secure fitment
- 10.00 x 20 - Available in Lug and Slick (Plain) pattern
- 14.00 x 24 & 14.00 x 25 - High profile version are available



SIZE (inch)	RIM WIDTH (inch)	OD (mm)	SW (mm)	# LOAD RATING (kg)		LUG	SMOOTH
				LOAD WHEEL	STEER WHEEL		
8.25 x 20	6.50/7.00/7.50	965	225	4400	2675	•	
9.00 x 20	6.50/7.00/7.50	985	225	5340	4450	•	
10.00 x 20 - 40	6.50/7.00/7.50	1026	242	5620	4650	•	•
11.00 x 20	7.50 / 8.00	1060	263	6510	5425	•	
12.00 x 20 - 42	7.50 / 8.00	1060	263	6510	5425	•	
12.00 x 20 - 42	8.00 / 8.50	1102	295	7500	6113	•	
12.00 x 20	10.00	1102	295	7500	6113	•	
12.00 x 24	8.50	1190	288	7980	6650	•	
12.00 x 24	10.00	1190	325	9000	7500	•	
14.00 x 24	10.00	1320	332	11000	9175	•	
14.00 x 25	11.25	1345	405	12480	10400	•	

OD - Overall Diameter SW - Section or Maximum Width #LOAD CAPACITY upto 25 kmph



**EMERALD RESILIENT TYRE MANUFACTURERS PVT. LTD.**  
 PLOT NO.2, 2ND STREET, PHASE 1  
 PORUR GARDEN, VANAGARAM  
 CHENNAI 600 095, INDIA  
**E-MAIL** enquiry@emeraldtyres.com  
**TEL** +91 44 6646 0555 / 0566  
**FAX** +91 44 6646 0550

**EMERALD MIDDLE EAST FZE**  
 P.O BOX 86009, RAKIA FREE ZONE  
 RAS AL KHAIMAH, U.A.E.  
**E-MAIL** info@emraldmiddleeast.com  
**TEL** +971 7 2433195  
**FAX** +971 7 2433189

**EMERALD TYRES EUROPE B.V.B.A.**  
 PATHOEKEWEG 130 C  
 8000 BRUGGE, BELGIUM  
**E-MAIL** info@emeraldtyres.com  
**TEL** +32 50310900



SOLID RESILIENTS • PRESS-ONS • DIRECT BONDING WHEELS • PU WHEELS • INDUSTRIAL PNEUMATICS  
 BUTYL TUBES & FLAPS • CONTAINER PADS • INDUSTRIAL WHEEL RIMS • FITMENT PRESS & FIXTURES

Emerald reserves the right to change the contents of this brochure without any prior notice