

SOLID RESILIENTS GRECKSTER™ CLASSIC

TIME-TESTED PERFORMANCE IN STANDARD WORKING CONDITIONS

Selecting the right type and version of tyre is significant in getting the optimum performance, maximum safety and extended tyre-life in a forklift besides ensuring value for the money spent on tyres. Emerald offers multiple versions in Solids that meet the varying demands of the application and work environment.

RESILIENTS ALSO AVAILABLE IN

AXIMO™ - ULTIMATE

for round the clock operations in strenuous work environment

EMPOWER™ - SUPER PREMIUM

for round the clock operations in tough work environment

GRECKSTER GOLD™ - PREMIUM

for round the clock operations

GRECKSTER MEO™ - STANDARD

for optimum performance in standard operating environment

ECOSTAR™ - ECONOMY

for nominal usage under normal working conditions

- Specialty versions include Non-Markers, Heat-Resistant, Oil-Resistant, Anti-Static, Aqua-Grip, Sub-Zero, Cut-Resistant, Anti-Abrasive, Anti-Skid tyres, etc., More info available on request.
- Tyres designed as per T&RA & ETRTO standards.

HEAVY-DUTY LOADING

EXCELLENT

LONG HOURS USAGE

GOOD

CUT/ABRASION RESISTANCE

GOOD

HEAT RESISTANCE

GOOD

ENERGY EFFICIENCY

GOOD

DRIVING COMFORT

EXCELLENT

- Load capacity in Kgs for Forklift truck used intermittently upto 25 KMPH.
- Recommended Distance coverage at a stretch is <2000 m (2 KM) as per international standards.

GRECKSTER™ CLASSIC
for Cost Effective Solutions

SIZE	Rim Width (inch)	Outer Diameter (inch)	Section Width (inch)	Load Capacity - Load Wheel (kg)	Load Capacity - Steer Wheel (kg)
3.00 x 4 (R)	2.10 / 2.50	9.90	3.30	260	195
3.50 x 4 (R)	2.50	10.00	3.50	260	195
4.00 x 4 (R)	2.50	11.80	3.60	525	410
3.20 - 8 (R)	3.00	8.90	4.05	770	590
4.00 x 8 (R/Y)	3.00 / 3.75	16.00	3.90	950	730
5.00 x 8	3.00 / 4.50 / 3.50 (Y) / 3.75(W)	17.90	4.90	1420	1090
6.00 x 9	4.00	20.60	5.60	1885	1450
15.00 x 4 ½ - 8 (125/75 - 8)	3.00 / 3.25	15.20	4.50	1040	800
16.00 x 6 - 8 (150/75 - 8)	4.33	16.00	6.40	1495	1150
18.00 x 7 - 8 (180/70 - 8)	4.33	18.00	5.90	2145	1650
18.00 x 9 - 8	7.00	18.00	8.00	2300	1900
21.00 x 8 - 9 (200/75 - 9)	6.00	20.70	7.60	2755	2120
20.00 x 6 - 9 (S)	4.00	19.45	5.50		
20.00 x 8 x 9 (S)	6.00	19.45	7.50		
4.00 x 9.75 (R)	3.75	16.80	4.80		
200 / 50 - 10	6.50	17.80	7.40	2470	1900
23.00 x 9 - 10 (225/75 - 10)	6.50	22.50	8.30	3445	2650
6.50 x 10	5.00	22.70	6.30	2340	1800
6.50 x 10	5.50	22.70	6.30	2570	1975
7.50 x 10	5.50	25.70	7.10	3070	2360
560 x 165 x 11	5.00	21.70	6.44		
23 x 10 - 12 (250/60 - 12)	8.00	23.30	9.65	3770	2900
7.00 x 12	5.00	25.40	6.90	2920	2240
27 x 10 - 12 (250/75 - 12)	8.00	25.60	9.80	3900	3000
28 x 12.5 x 15 (355/45 - 15)	9.75	27.10	12.40	5525	4250
32 x 12.1 x 15 (355/65 - 15) (350 - 15)	9.75	32.28	11.80	7800	6000
250 x 15 (250/70 - 15)	7.00 / 7.50	28.90	9.30	4750	3650
300 x 15 (315/70 - 15)	8.00	32.30	10.10	5850	4500
6.00 x 15	4.50	27.40	5.90	2455	1820
7.00 x 15	5.50 / 6.00 / 6.50	27.60	7.50	3545	2725
7.50 x 15	5.50 / 6.00 / 6.50	28.30	7.50	3900	3000
8.15 x 15 (225/75 - 15) (28 x 9 - 15)	7.00	27.10	8.40	3445	2650
8.25 x 15	5.50 / 6.50	30.70	7.90	4750	3650
7.50 x 16	5.50 / 6.00	30.80	7.90	3908	2831
8.00 x 16	5.50			3965	3050
8.25 x 16	6.00	30.75	8.00		
7.50 x 20	6.00	34.75	7.05	3840	3200
8.25 x 20	6.50 / 7.00	38.90	9.10	4400	3675
9.00 x 20	7.00 / 7.50 / 8.00	40.40	9.50	5340	4450
10.00 x 20	7.50 / 8.00	40.40	9.50	6000	5000
11.00 x 20	7.50 / 8.00	41.40	10.35	6510	5245
12.00 x 20 - 42	8.00	41.40	10.35	6510	5245
12.00 x 20 - 43	8.00 / 8.50	43.40	11.60	7500	6250
14.00 x 20 (S)	10.00	48.80	13.10	8250	6800
12.00 x 24	8.50 (S) / 10.00 (Y)	47.00	11.80	7980	6650
14.00 x 24	10.00	51.20	13.20	11000	9175

- Load capacity in Kgs for Forklift truck used intermittently upto 25 KMPH.
- Recommended Distance coverage at a stretch is <2000 m (2 KM) as per international standards.

All dimensions are nominal only



Emerald – the market leader and an emerging global player from India offers range of products to provide Total Tyre-Wheel assembly solutions for the Material Handling Industry. The company having network of sales office, warehouse and dealers located all over India and overseas serves its customer with Just In Time delivery, Fitment solutions from proximal locations.

EMERALD TYRE MANUFACTURERS LIMITED

REGISTERED OFFICE & MARKETING OFFICE

EMERALD HOUSE, PLOT NO.2, 2ND STREET, PHASE 1, PORUR GARDEN VANAGARAM, CHENNAI 600 095, TAMIL NADU, INDIA

INTERNATIONAL

E-MAIL • crm2@emeraldtyres.com • vkr@emeraldtyres.com
TEL • +91 44 6646 0511 MOBILE • +91 99405 40100

DOMESTIC

E-MAIL • crm@emeraldtyres.com • dek@emeraldtyres.com
TEL • +91 44 6646 0528 MOBILE • +91 99406 40100

FACTORY

PLOT NO.78, 79 & 80, EPIP ZONE, SIPCOT INDUSTRIAL COMPLEX GUMMIDIPOONDI, TIRUVALLUR DISTRICT, TAMILNADU 601 201, INDIA
TEL • +91 44 6790 5508

EMERALD MIDDLE EAST FZE

SMBA0479 COMPASS BUILDING, AL SHOHADA ROAD AL HAMRA INDUSTRIAL ZONE-FZ, RAS AL KHAIMAH UNITED ARAB EMIRATES
E-MAIL • asrajesh@emrldmiddleeast.com
TEL • +971 50 115 2059

EMERALD TYRES EUROPE B.V.

WARANDESTRAAT 1A, 9240 ZELE, BELGIUM (OFFICE)
LINDESTRAAT 10, 9240 ZELE, BELGIUM (WAREHOUSE)
E-MAIL • ddaniel@emeraldtyres.com
TEL • +32 468 156 310

SA RUBBER ENGINEERING (PTY) LTD.

LANCASTER ROAD, ACTONVILA POPLAR SECURE BUSINESS PARK, INIT 12, 16 BENONI 1506, SOUTH AFRICA
E-MAIL • vts@forktyre.co.za
TEL • +27 66 449 1548

SOLID TYRE • PRESS-ON TYRE • CURED-ON TYRE (DIRECT BONDING WHEEL) • INDUSTRIAL PNEUMATIC TYRE BUTYL TUBE & FLAP • WHEEL RIM • FITMENT PRESS AND FIXTURES

Emerald reserves the right to change the contents of this brochure without any prior notice

